

# 1520

## VAPOR RECOVERY CAM-LOCK



CE Ex II 2G

The 1520 Vapor Recovery Coupler is a 100-mm (4") female camlock coupler that is designed to be connected to any hose adapter and allows the vapor transfer to the tank truck during loading operation.

It guarantee security for the operator.

Vapor recovery coupler CAMLOCK 4" is used in the vapor recovery line (Stage 1) according to Directive ATEX 2014/34/UE and harmonized standard.



### Specification

<b>CODE</b>	<b>1520-00</b>
<b>BODY</b>	ALUMINIUM
<b>PIN</b>	BRASS
<b>GASKET/OR</b>	NBR
<b>COUPLER SIZE</b>	CAM-LOCK 4"
<b>FITTING END SIZE</b>	3"M-2"1/2F BSPP
<b>PRESSURE TEST</b>	0,5 bar
<b>OPERATING TEMPERATURE</b>	-20°/+60°C

### Chemical Suitability

- Standard Model is for traditional fuel without additives or compatible chemical products

## Installation

- The foot valve is normally installed at the bottom of the suction line of the storage tank in such a way in order to always ensure the pressure in the suction tube.
- For correct installation follow the Directives and product User Manual.
- For custom application or maintenance write to: [quality@ridart.it](mailto:quality@ridart.it)
- Declaration of Conformity and User Manual are available on: [www.ridart.it/support](http://www.ridart.it/support)

## Maintenance

- Periodically check the device is necessary to remove possible dirty.
- Always replace the product after fire or deflagration.
- In case of tampering warranty expires and safety protection is not guaranteed.